



SUPERSPORT



BEST PRACTICE

NASCAR CUP SERIES
GT-ENDURANCE

Product name	SUPERSPORT
Product code LH Version	SUPERSPORT.01
Product code RH Version	SUPERSPORT.02
Product code UH Version	SUPERSPORT.03

Drive shaft	Spline Drive
Weight	4,03 kg (8.9 lbs)
Length	202 mm (7.95")
Air inlet	3/8" BSP
Supply hose inside diameter	13 mm (0.51")
Max pressure	25 bar (362 psi)
Free Speed (25 bar / 362 psi)	LH / RH 11500 rpm UH 11000 rpm
Max torque	LH / RH 3500 Nm (2590 ft-lbs) UH 2800 Nm (2065 ft-lbs)
Gun selector plate	2 port

ALSO AVAILABLE

Product name	SUPERSPORT SQUARE DRIVE
Drive shaft	
Product code LH Version	SUPERSPORT.04
Product code RH Version	SUPERSPORT.05
Product code UH Version	SUPERSPORT.06

AVAILABLE VERSIONS



Fast left hand version: loosens nuts tightened clockwise faster



Fast right hand version: loosens nuts tightened anticlockwise faster



Special unhandled version: loosens at same speed both the nuts tightened clockwise and anticlockwise

HIGHLIGHTS

- Radial Hammer Mechanism



NEW FAST REVERSE SYSTEM

Longer and easier to move. Positioned on the side where the rotation reverse mechanism turns from loosening to tightening.

NEW FRONT COVER SHAPE

AEROSPACE ALUMINIUM FRONT COVER



NEW OPTIONAL MONOLITHIC PIN



SQUARE DRIVE READY



BUILT-IN FRS

NEW RADIAL HAMMER MECHANISM (RHM) INSIDE!

The new radial hammer mechanism guarantees a superior performance and a longer lifespan of the hammer mechanism parts, thanks to the new developed geometry.



ALREADY INCLUDED! TO INCREASE DURABILITY AND STRENGTH

SUGGESTED COUPLINGS & FITTINGS

- couplings: minimal bore of 10 mm (25/64")
- Inlet made by steel

MANUAL



Operating and Maintenance Manual